



103 Master Trax Lite™




- Durable 9 mm thick carpet flooring, designed for large indoor entrance areas, including wall-to-wall application. Offers many possibilities or creative combinations that will allow the entrance to become part of the complete interior design.
- Unsurpassed ability to retain moisture and scrape debris from foot traffic while maintaining its great looking appearance for the longest time.
- Mold and mildew resistant, UV stabilized, crush resistant and remains unaffected by climate extremes.
- Suitable for even the heaviest of traffic conditions.
- For placement inside entrances or outside if not exposed to rain.
- In recess frames (depth 10 mm) or wall to wall installations in shopping malls, airports, hospitals, hotel lobbies, banks, restaurants, golf facilities (spikes resistant), fitness centers, elevators, locker rooms, ski lodges, skating rinks, automobile showrooms, any public or professional building.
- Vacuum/shampooing or use extraction method to clean.



Blue



Brown




Charcoal



Red



Grey



Autumn Ochre



Autumn Burgundy



Green

103 Master Trax Lite™

PRODUCT SPECIFICATIONS			
Designation		Dust Control Matting	
Description		Absorbent / scrape carpet mat	
Type			
Material			
	Top	Nibbed needle punched carpet consisting of anti-static 100% polypropylene fibers. 1200 grams of yarn per m².	
	Backing	Synthetic rubber (rolls)	
Process		Non woven/Needle punched	
Category		Indoor absorbent - Contract	
Recommended use		Indoor - heavy traffic areas - recess frames, wall to wall, finished mat	
Colours		Blue, Brown, Charcoal, Red, Grey, Autumn Burgundy, Autumn Ochre, Green	
Weight		2,2 kg/m²	
Thickness		9 mm	
Standard sizes		Full rolls: 200 cm x 21 m	
Custom sizes		N/A	
Special remarks		Crush resistant and unaffected by climate extremes. Mold/mildew resistant. Easy to install, can be cut to any size or shape without edge ravel.	
PRODUCT TESTING			
Tests		Norms	Results
Abrasion resistance		ASTM D3884	
Colour fastness to light		AATCC 16E	
Accelerated wear test by sim floor machine		U.S.	
Accelerated soiling		U.S.	
Anti-slip		DIN51130 BGR181	
Water retention		U.S	4 l/m²
Sanitary epidemiologic test		GN 2.1.6.1338-03 MCL GN 2.1.6.2309-07 OBUV	Pass - Certificate no. 77.01.16.229.P.044984.07.09
FIRE TESTING			
	Surface Flammability	ASTM D2859	Pass
	Classification of the reaction to fire performance	DIN EN 13501-1	
	Russian fire retardancy test	CCPB.NLOP-019.B01723	Pass
Sustainability		<ul style="list-style-type: none">• Recyclable material• REACH compliant (Registration, Evaluation, Authorization and restrictions of Chemicals)• Contributes to cleaner environment by reducing need of cleaning chemicals	