123 Polyplush Lite™



- sellers for use in moderate foot traffic.
- Vinyl backing is moisture resistant, slip resistant and will not stain floor.
- Suitable for light traffic conditions.
- For placement inside entrances of offices, shops.
- Vacuum clean.
- Free of toxic DOP and DMF.

123 Polyplush Lite™

			PRODUCT SPECIFICATIONS		
Designation		Dust Control Matting			
Description		Absorbent carpet mat			
Material					
		Tufted cut pile carpet 30 grams of yarn per r	t made of 100% Polypropylene yarns. m².		
Backing Black vinyl (DOP free)		Black vinyl (DOP free)			
Process		Tufted			
Category		Indoor absorbent - Bestseller			
Recommended use		Indoor - light to medium traffic conditions			
Colours		Brown, Red, Blue, Grey			
Weight		2.4 kg/m ²			
Thickness		4.5 mm			
Standard sizes		60 cm x 90 cm 90 cm x 150 cm 120 cm x 180 cm 90 cm x 20 m 120 cm x 20 m			
		90 cm and 120 cm per	m and 120 cm per linear meter		
Special remarks		1			
-1			PRODUCT TESTING		
	Te	ests	Norms	Results	
Abrasion resistance			ASTM D3884	1100 0110	
Colour fastness to light		t	AATCC 16E		
Accelerated wear test by sim floor machine			U.S.		
Accelerate		.,	ASTM 6540		
Anti-slip			DIN51130 - BGR181		
Water retention			ISO 4920 TNO W6034		
Sanitary epidemiologic		test	GN 2.1.6.1338-03 MCL GN 2.1.6.2309-07 OBUV		
Graves tea	r strength				
Breaking load			ASTM D412		
Elongation					
Hexapod tumble drum tester		tester	ASTM D5252		
			FIRE TESTING		
		Surface Flammability	ASTM D2859	Pass	
		Classification of the reaction to fire performance	DIN EN 13501-1	Efl-S1	
Sustainability			Recyclable material REACH compliant (Registration, Evaluation, Authorization and restrictions of Chemicals) Contributes to cleaner environment by reducing need of cleaning chemicals		

